

Polyflow®-G Filter Cartridge

All-polypropylene nominal-rated depth cartridges for economical prefiltration

Polyflow®-G depth media has been developed for a wide variety of general process applications from fluid clarification to general prefiltration. Its high dirt-loading, random-fiber polypropylene depth media provides consistent particle retention.

Polyflow-G is thermally bonded from 100% virgin polypropylene to ensure clean filtrates and excellent chemical and thermal compatibility in the most demanding processing conditions.

Polyflow-G leads in overall reduction of filtration costs when compared to spunbonded, stringwound, and nominally-rated pleated prefilter cartridges. Its longer filtration life reduces downtime due to fewer change-outs.



Contact Information

Parker-Hannifin Corporation
Bioscience & Water Filtration Division
2340 Eastman Avenue
Oxnard, California, USA 93030

toll free +1 877 784 2234
phone +1 805 604 3400
fax +1 805 604 3401
bioscience.na@parker.com

www.parker.com/bioscience

Benefits

- High flow rate and long service life reduce processing time
- Broad chemical compatibility allows use in most applications
- Thermally bonded construction minimizes extractables for cleaner filtrates

Applications

- Solvent filtration
- Liquid clarification
- Recirculating liquids
- General water filtration
- Reagent grade chemicals
- RO/DI prefiltration
- Waste water



ENGINEERING YOUR SUCCESS.

Polyflow®-G Filter Cartridge

SPECIFICATIONS

Materials of Construction

Depth media: Polypropylene
 Support layers: Polypropylene
 Structure: Polypropylene
 All components are thermally bonded to ensure integrity and to reduce extractables.

Nominal Filter Ratings

0.2µm, 0.5µm, 1µm, 3µm, 10µm, and 30µm

Effective Filtration Area

3.6ft² (0.33 m²) per 10" (250mm) cartridge

Cartridge Extractables

NVR < 35mg per 10" (250mm) cartridge

Maximum Differential Pressure/ Temperature

Forward: 80psid (5.5bar) @ 75°F (24°C)

Reverse: 40psid (2.8bar) @ 75°F (24°C)
 15psid (1.0bar) @ 140°F (60°C)


Maximum Operating Temperature

160°F (71°C)

Performance Attributes

Water flow rates, Typical*		
Micron	gpm/psid	lpm/100mbar
0.2	4.2	23
0.5	11.0	60
1.0	33.0	181
3.0	70.0	384
5.0	70.0	384
10.0	70.0	384
30.0	70.0	384

* Per 10-inch (250mm) cartridge equivalent.



Ordering Information

Each cartridge is identified with a product number, pore size and lot number for traceability.

PG — **0** — —

Styles		End Fitting		Nominal Length			Filter Rating		Gasket O-Rings		Gasket Only			
CODE	DESCRIPTION	CODE	DESCRIPTION	CODE	INCHES	mm	CODE	MICRON	CODE	MATERIAL	CODE	THICKNESS	INCHES	mm
1	None	0	DOE (Cuno®)	05	5"	125	002	0.2	0	Buna-N	1	0.200"	5	
A	½" Shortened on 222 Fitting	1	DOE	10	10"	250	005	0.5	1	EPDM	2	0.125"	3	
		2	226 Flat	20	20"	500	010	1.0	2	Silicone	4	(1) 0.200"	5	
		3	222 Flat	30	30"	750	030	3.0	4	Viton®	5*	(1) 0.125"	3	
		6	020 Internal Flat	40	40"	1000	050	5.0	5*	FEP Encapsulated Viton®	6*	No Gasket		
		7	226 Fin				100	10.0	N	FEP Encapsulated Silicone				
		8	222 Fin				300	30.0		N	None			
		G	120 Internal Recessed End cap											
		H	213 Recessed End cap (Ametek)											
		J	120 O-ring/Fin											
		R	222 Recessed End cap											

*O-Rings only

Specifications are subject to change without notification.
 For User Responsibility Statement, see www.parker.com/safety
 Polyflow is a registered trademark of Parker-Hannifin Corporation.
 Viton is registered trademark of E.I. DuPont de Nemours & Co., Inc.
 Cuno is a registered trademark of 3M Company.
 Ametek is a registered trademark of Ametek, Inc.

© 2018 Parker-Hannifin Corporation, Bioscience & Water Filtration Division
 All Rights Reserved

DS_ME_Polyflow-G Rev. C



WARNING: This product can expose you to chemicals including 1,3-Butadiene which are known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

ENGINEERING YOUR SUCCESS.